

MATERIAL SAFETY DATA SHEET

Elementis Pigments Inc.
11 Executive Dr., Suite 1
Fairview Heights, IL 62208

Product: Ferrispec™ FP Fine Powder - Black
MSDS No. PIGMENT / EPI-001
Revision: Original
Date: August 2000

HAZARD MATERIAL IDENTIFICATION SYSTEM

Health Hazard	0 - Minimal
Flammability Hazard	1 - Slight
Reactivity Hazard	0 - Minimal
Personal Protection	E - Glasses, Gloves, Dust Resp

SECTION I. MATERIAL IDENTIFICATION

Trade/Material Name: Black Iron Oxide

Description: Black Iron Oxide, C.I. Pigment Black 11, C.I. No. 77499

Other Designations: BK4799, BK5000, BK5099, BK5599, BK5799

CAS: 1317-61-9 (may also be described as CAS # 12227-89-3)

Chemical Name: Fe₃O₄

MANUFACTURER: Elementis Pigments Inc. PHONE: 618-271-4700
11 Executive Dr., Suite 1 E. St. Louis Plant
Fairview Heights, IL 62208

SECTION II. INGREDIENTS AND HAZARDS

<u>INGREDIENT NAME:</u>	<u>CAS NUMBER:</u>	<u>PERCENT</u>	<u>EXPOSURE LIMITS(1)</u>	
Iron Oxide Black	1317-61-9	>99%	OSHA PEL:	15 mg/M ³ TWA
			ACGIH TLV:	10 mg/M ³ TWA

(1) Nuisance dust

(Ingredients and Hazards continued on next page)

(Ingredients and Hazards continued from previous page)

SARA TITLE III: Section 313 Supplier Notification

This product does not contain toxic chemicals subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40 CFR 372.

<i>SECTION III.</i>	<i>PHYSICAL/CHEMICAL CHARACTERISTICS</i>
---------------------	--

<u>Appearance and Odor:</u>	Black Powder, No Odor
Solubility in Water (%): Insoluble	
Specific Gravity (H ₂ O=1):	4.8 – 5.1
% Volatile by Volume	0

<i>SECTION IV.</i>	<i>FIRE AND EXPLOSION DATA</i>
--------------------	--------------------------------

<u>Flashing Point(method):</u>	Not flammable, but may be subject to slow oxidation if stored at temperatures above 140°F.
<u>Extinguishing Media:</u>	Not flammable. Use appropriate extinguishing media for the combustible material involved in the fire. If oxidation should occur, heat will be liberated which could cause surrounding combustibles to burn. If oxidation starts, the pallet should be broken apart and cooled with water and dissipate the heat.
<u>Unusual Fire or Explosion Hazards:</u>	Storage at temperatures above 140°F may cause the black iron oxide to oxidize, generating heat which could cause surrounding combustibles to burn.
<u>Special Firefighting Procedures:</u>	Firefighters should wear self-contained breathing apparatus.

<i>SECTION V.</i>	<i>REACTIVITY DATA</i>
-------------------	------------------------

Material is not stable if stored at temperatures above 140°F.- Hazardous polymerization will not occur

<u>Chemical incompatibilities:</u>	It is incompatible with strong oxidizing agents.
<u>Conditions to avoid:</u>	Storage above 140°F.
<u>Hazardous Decomposition Products:</u>	None

SECTION VI.

HEALTH HAZARD DATA

This product is not considered a carcinogen by IARC, NTP, ACGIH or OSHA

<u>Summary of Health Risks and Symptoms of Exposure:</u>	May cause mechanical skin and eye irritation. Repeated and prolonged exposures to iron oxide dust may cause a benign pneumoconiosis called siderosis
<u>Principal Routes of Entry:</u>	Inhalation, ingestion
<u>Acute Effects:</u>	Causes mechanical skin and eye irritation
<u>Chronic Health Effects(s):</u>	Prolonged inhalation of iron oxide dust is known to produce a condition known as siderosis. On X-rays it appears to be a benign pneumoconiosis and is not associated with pulmonary fibrosis producing materials such as silica. The TLV is set to protect against siderosis.
<u>Emergency and First Aid Procedures:</u>	
Eye Contact:	Flush eyes with generous amounts of water for at least 15 minutes. Call a physician if irritation persists.
Skin Contact:	Wash dust from skin with mild soap and water.
Inhalation:	Remove to fresh air. Call a physician.
Ingestion:	If conscious, give large quantities of water to induce vomiting. Get medical attention.

SECTION VII.

PRECAUTIONS FOR SAFE HANDLING, USE OR DISPOSAL

<u>Spill / Leak procedures:</u>	Vacuum or use wet clean-up techniques and place waste material in closed container.
<u>Waste management / disposal:</u>	Disposal must be made in accordance with Federal, State and local regulations. Pursuant to 40 CFR part 261 of the Resource Conservation & Recovery Act (RCRA). CERCLA or DOT Regulations currently in effect, discarded Carbon Black would not be classified as a hazardous waste.
<u>Precautions to be taken in handling and storing:</u>	For transportation emergencies, call CHEMTREC, 24 hour information service, (800) 424-9300.

SECTION VIII.

SPECIAL PROTECTION INFORMATION

Personal protective equipment:

- Goggles: Safety glasses or dust-tight goggles
- Gloves: Leather or rubber gloves.
- Respirator: Use of NIOSH approved dust respirator is recommended when exposure limits may be exceeded.

Workplace Considerations:

- Ventilation: Local exhaust ventilation to collector or containment recommended to control dust to below exposure limits.
- Safety Stations: An eye wash station should be available to the area of use.
- Other: In accordance with good industrial hygiene practice, avoid contact with skins, eyes or clothing. Avoid breathing dust. Keep container closed when not in use. Use with adequate, localized ventilation. Wash thoroughly after handling and before eating, drinking or using tobacco products.

SECTION IX.

SPECIAL PRECAUTIONS

DOT Class: Not regulated

The information presented herein is believed to be accurate and was obtained from sources believed to be reliable. However, the information is provided without any representation or warranty, expressed or implied, with respect to its accuracy or completeness. It is the users' responsibility to determine the suitability of this product and the relevance of this information for their use. Elementis Pigments Inc. does not assume liability resulting from the use, handling, storage, and disposal of this product.