



MATERIAL SAFETY DATA SHEET

Ferro Corporation
Performance Pigments & Colors
251 West Wylie Ave.
Washington, PA 15301 USA

Emergency telephone number
CHEMTREC: 1-800-424-9300
CHEMTREC (outside U.S.): 1-703-527-3887
Phone Number: 1-724-223-5900

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

Product Name: 41545A Yellow Spersastain
DRM100LB
Date of Preparation: 12/21/2011

Chemical Family: Inorganic Pigment
CAS-No.: Mixture
Product Code: 1133463

2. HAZARDS IDENTIFICATION

Emergency Overview

Caution

May cause respiratory tract, eye and skin irritation. Avoid dust formation. Contains crystalline silica which causes silicosis and lung cancer.

		HMIS	NFPA 704
Color:	Yellow	1*	1
Physical state:	Powder	0	0
Odor:	Odorless	0	0
		E	

Potential Health Effects

Principle routes of exposure: Inhalation, ingestion, skin and eye contact.

Eye contact: May cause slight irritation.

Skin contact: Prolonged skin contact may cause skin irritation and/or dermatitis.

Inhalation: May cause irritation of respiratory tract.

Ingestion: May irritate digestive tract.

Chronic toxicity: Excessive inhalation of dust may cause chemical pneumonitis, cyanosis, and pulmonary edema. Respirable crystalline silica has been classified as a Group I (sufficient evidence in humans for carcinogenicity) carcinogenic by IARC and is listed by NTP as a substance which may reasonably be anticipated to be a carcinogen. Long term inhalation causes lung damage (silicosis and cancer).

3. COMPOSITION/INFORMATION ON INGREDIENTS

Components	CAS Number	Weight %
Zircon praeaseodymium yellow	68187-15-5	80 - 90%
Quartz silica	14808-60-7	10 - 20%
Silica, fumed	112945-52-5	1 - 5%

This product contains trace quantities of naturally occurring radioactive uranium, thorium and radium (<0.02% total). Overexposure by inhalation to respirable dusts containing uranium, thorium and radium may cause cancer, however, observance of the OSHA limit for respirable dusts of 5 mg/m³ will ensure the use of this product to be well below the regulatory limits established for these components.

4. FIRST AID MEASURES

Eye contact:	Rinse immediately with plenty of water, also under the eyelids. Get medical attention if irritation develops.
Skin contact:	Wash off immediately with soap and plenty of water. Remove and wash contaminated clothing before re-use. If symptoms persist, call a physician.
Inhalation:	Move to fresh air. If breathing is difficult, give oxygen. If symptoms persist, call a physician.
Ingestion:	Drink plenty of water. Do not induce vomiting. Consult a physician if necessary.
Notes to physician:	Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flash point (°C):	Non combustible
Suitable extinguishing media:	Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. The product itself does not burn.
Hazardous decomposition products:	Metal fumes.
Special protective equipment for firefighters:	As in any fire, wear self-contained breathing apparatus (pressure-demand, NIOSH approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:	Avoid dust formation. Evacuate area of all unnecessary personnel. Avoid contact with skin, eyes and clothing. Wear personal protective equipment. Ensure adequate ventilation.
Environmental precautions:	Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Do not flush into surface water or sanitary sewer system.
Methods for cleaning up:	Wear personal protective equipment. Sweep up and shovel into suitable containers for disposal. Clean contaminated surface thoroughly. Dispose of promptly.

7. HANDLING AND STORAGE

Handling:	Handle in accordance with good industrial hygiene and safety practice. Avoid dust formation. Avoid contact with skin, eyes and clothing. Wash hands thoroughly before eating, drinking or smoking. In case of insufficient ventilation, wear suitable respiratory equipment. Provide appropriate exhaust ventilation at places where dust is formed. Do not take internally. Wash thoroughly after handling. Use only in well-ventilated areas.
Storage:	Keep container tightly closed in a dry and well-ventilated place. Store in original container.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limits

Minimize exposure in accordance with good hygiene practice.

Components	OSHA	ACGIH
Zircon praseodymium yellow	5 mg/m ³ TWA Zr	10 mg/m ³ STEL Zr 5 mg/m ³ TWA Zr
Quartz silica	Listed	0.025 mg/m ³ TWA respirable fraction

Engineering measures:	Provide appropriate exhaust ventilation at machinery and at places where dust or fumes can be generated. Ensure adequate ventilation, especially in confined areas. Ensure that eyewash stations and safety showers are proximal to the work-station location.
------------------------------	--

Eye protection:	Safety glasses with side-shields.
Skin and body protection:	Lightweight protective clothing. Keep working clothes separately. Remove and wash contaminated clothing before re-use.
Hand protection:	Impervious gloves.
Respiratory protection:	NIOSH-approved respirators should be worn where engineering controls and work practices do not reduce exposure to or below the PEL. Wear NIOSH approved respirator to limit exposure to NORM. In case of insufficient ventilation wear suitable respiratory equipment . Seek professional advice prior to respirator selection and use.
Hygiene measures:	Wash hands before breaks and at the end of workday. Contaminated work clothing should not be allowed out of the workplace. Ensure that eyewash stations and safety showers are proximal to the work-station location.

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	Yellow	Physical state:	Powder
Odor:	Odorless	Molecular weight:	No data available
Boiling point/range (°C):	No data available	pH:	No data available
Melting point/range (°C):	No data available	Specific gravity (Water =1):	No data available
Vapor density:	Non-volatile	Vapor pressure :	No data available
Evaporation Rate (Water = 1)	Non-volatile	Water solubility:	Insoluble
VOC content (%)	0		

10. STABILITY AND REACTIVITY

Stability:	Stable at normal conditions.
Polymerization	Will not occur.
Hazardous decomposition products:	None under normal use.
Materials to avoid:	None known.
Conditions to avoid	None known.

11. TOXICOLOGICAL INFORMATION

Acute toxicity:	Information given is based on data on the components and the toxicology of similar products
Chronic Toxicity:	Contains crystalline silica which causes silicosis and lung cancer.
Carcinogenic Effects:	Respirable crystalline silica has been classified as a Group I (sufficient evidence in humans for carcinogenicity) carcinogenic by IARC and is listed by NTP as a substance which may reasonably be anticipated to be a carcinogen. Crystalline silica is also a known cause of silicosis, a non-cancerous lung disease caused by excessive exposure to crystalline silica.
Target Organ Effects:	Silica: Respiratory system.

Component information, if any, is listed below

Quartz silica

LD50s and LC50s:	Oral LD50 (Rat) = 500 mg/kg
OSHA - Select Carcinogens:	Present
NTP:	Known Human Carcinogen
IARC - Group 1:	Listed

Silica, fumed

LD50s and LC50s:	Oral LD50 (Rat) = 3160 mg/kg
-------------------------	------------------------------

12. ECOLOGICAL INFORMATION

Aquatic toxicity: No data is available on the product itself. Information given is based on data on the components and the ecotoxicology of similar products.

Persistence and degradability: Not determined

13. DISPOSAL CONSIDERATIONS

Waste from residues / unused products: Waste must be disposed of in accordance with federal, state and local environmental control regulations. Where possible recycling is preferred to disposal or incineration. This product contains Naturally Occuring Radioactive Materials (NORM). Consult and comply with current regulations.

14. TRANSPORT INFORMATION

DOT (U.S.)

Proper shipping name: Not regulated.

TDG (Canada)

Proper shipping name: Not regulated.

15. REGULATORY INFORMATION

U.S. Regulations:

TSCA: Not subject to TSCA 12(b) Export Notification

SARA 313: Not subject to the provisions of SARA 313 Title III

State Regulations

This product or its ingredients have been evaluated for New Jersey, Pennsylvania, and California Prop 65 supplier notification requirements. Substances that are subject to notification requirements, if any, are listed below.

Components	NJRTK:
Quartz silica	Listed (NJRTK)

Components	State Regulation - CA Prop65
Titanium Dioxide	Carcinogen
Quartz silica	Carcinogen

Canadian WHMIS

WHMIS hazard class: D2A Very toxic materials

Canadian Ingredient Disclosure List (IDL):

Components	Canada - WHMIS Ingredient Disclosure:
Quartz silica	1

International Inventories

TSCA 8(b): Listed or exempt.
Canadian DSL/NDSL list All ingredient(s) are listed on the DSL or NDSL
EC-No. Listed or exempt.
Philippines (PICCS): Listed.
Japan (ENCS): Listed or exempt.
Korea (KECL): Listed.

China (IECS):	Listed.
Australia (AICS):	Listed.
New Zealand (NZIoC):	Listed.

16. OTHER INFORMATION

For Industrial Use Only.

Prepared by: Ferro Technical Center

The information and recommendations contained in this Material Safety Data Sheet have been compiled from sources believed to be reliable and to represent the most reasonable current opinion on the subject when the MSDS was prepared. No warranty, guaranty or representation is made as to the correctness or sufficiency of the information. The user of this product must decide what safety measures are necessary to safely use this product, either alone or in combination with other products, and determine its environmental regulatory compliance obligations under any applicable federal or state laws.

End of Safety Data Sheet