



Distributed by:
 Laguna Clay Company
 14400 Lomitas Ave
 City of Industry, CA 91746
 1-800-4Laguna
 info@lagunaclay.com
 www.lagunaclay.com



Material Safety Data Sheet

Product Name FRIT 201	Note: Do not leave fields blank. IF some point does not apply or is not specified, must be identified as follows: N / A: Not Applicable N / S: Not Specified
--	--

Section I: Identification of the Manufacturer

Name of Manufacturer MACESA Fritas	In an emergency call: (01152) 81 24 81 99
Address: BOULEVARD DIAZ ORDAZ Km. 335.5 GARZA GARCIA, N.L. MEXICO CP 66230	For Information call: (01152) 81 24 82 34
	Preparation date: 10/3/2011
	Sign

Section II: Hazardous Ingredients

Component Name	No. CAS	Concentration (%)	OSHA PEL (mg/m3)	ACGIH TLV (mg/m3)	Other Limits Recommended
1 Silca	14808-60-7	35 - 40 %	10 % / SiO2 +2	0.025	N/S
2 Calcium carbonate	471 -34-1	25-30 %	N/S	N/S	N/S
3 Sodium tetraborate pentahydrate	N/S	35-40 %	N/S	N/S	N/S

Section III: Physical and Chemical Characteristics

Boiling point	N/A	Specific Gravity (H2O = 1)	N/S
Vapor Pressure (mmHg)	N/A	Melting point	N/S
Vapor Density (Air = 1)	N/A	Evaporation Ratio (butylacetate = 1)	N/A
Water solubility: Insoluble	Appearance and Odor: Powder, odorless. Color may vary.		

Section IV: Fire and Explosion

Flash Point (include method of determining) N/A	Flammability Limits	Inferior N/A	Superior N/A
Extinguishing Media No danger of fire			
Special procedures for fire fighting No danger of fire			
Unusual danger and explosion Not required			

Section V: Reactivity

Unstable	N/A	Conditions to avoid
Stable	Stable	Avoid contact with acids (eg, acetic, hydrofluoric, etc.).
Incompatibility (Materials to Avoid) Avoid contact with acids (eg, acetic, hydrofluoric, etc.).		
Hazardous Decomposition Products: Under normal conditions, this product does not release after the application materials		
Hazardous Polymerization:	N/A	Conditions to avoid N/A

Section VI: Health Hazards

Route of Entry:	Inhalation <u>NO</u>	Skin <u>SI</u>	Ingestion <u>NO</u>
Health Hazards (Acute and Chronic) Acute: Improper handling of chips, without the appropriate PPE, can cause small lesions in contact with skin and eyes			
Chronic: Excessive inhalation of respirable crystalline silica can cause silicosis.			
The International Agency for Research on Cancer (IARC) concluded that there is evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz from occupational sources.			
Cancer risk	NTP? <u>YES</u>	IARC Monograph <u>YES</u>	OSHA Regulated <u>YES</u>
Symptoms of Exposure Excessive exposure to dust from the chip without the proper PPE, may irritate eyes, skin and respiratory tract			
Medical conditions aggravated by exposure Workers with poor respiratory capacity should have limited exposure to this material.			
Emergency procedures and first aid. Skin: Wash with soap and clean water to the affected area Inhalation: Remove the person from exposure, moving to a place with clean, fresh air, if breathing has stopped, provide artificial respiration. Seek medical attention Ingestion: Get immediate medical attention Eyes: Remove the person from exposure and flush the eye with large amounts of clean water, lifting the upper eyelid and down the bottom repeatedly. If irritation persists get medical attention.			

Section VII: Procedures for safe handling and use

Procedure in case of spills Use appropriate PPE. Do not dry sweep, proceed to your collection, with a practice that eliminates the generation of dust (which may include wet methods or vacuum).
Disposal method Place material in suitable containers, identified and provided in accordance with federal, state and local
Precautions for handling and storage NOT REQUIRED
Other Precautions Use appropriate gloves to work with frit

Section VIII: Personal Protective Equipment

Respiratory Protection (Specify Type): NOISH approved dust and mist
Ventilation: Use adequate ventilation to maintain dust exposure below recommended limits. Avoid breathing dust. The greatest potential for exposure to silica occurs during dry conditions. Wet methods are recommended
Eyes: Use safety glasses or goggles. Do not use contact lenses in work areas.
Skin: Use cotton gloves or skin to minimize exposure of the skin. Wash hands with soap and water before eating, drinking, smoking and end of the <u>workday, after working with frit.</u>
Other clothing and equipment Note: Personal protection information indicated in this document is based on general information under normal conditions. Where special or unusual conditions exist, we suggest the assistance of a qualified professional in security.

Section IX: Regulations

SARA Report N/A
Regulations for the Transportation (DOT) This material is considered as non-hazardous for ground transportation and / or Air
(TSCA) The components of this product have been introduced in the U.S. trade and are listed in the inventory of TSCA (Toxic Substance Control Act)